

# SERVI-BOND™ Shield Connector

**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

## Description

The **SERVI-BOND Shield Connector** is designed to assure shield continuity to a point of ground for buried telephone service wires.

## Features

- Easily installed and requires no special tools.

## Documentation

### Application Procedures

[SP-2691 \(SERVI-BOND Shield Connector\)](#)

## Catalog Pages

[SERVI-BOND Shield Connector - Catalog](#)

## Part Tables

Catalog Number (mm)	Spring Clamp Color Code	Maximum Service Wire Diameter inches (mm)	Service Cable Range
8000733* (long neck)	Silver	0.30 (8)	2-Pair or 3-Pair (Armored and Non-Armored)
8000734 (long neck)	Yellow	0.36 (9)	5-Pair or 6-Pair (Non-Armored)
	Black	0.41 (10)	5-Pair or 6-Pair (Armored)
8000735 (short neck)	Silver	0.30 (8)	2-Pair or 3-Pair (Armored and Non-Armored)
8000736 (short neck)	Yellow	0.36 (9)	5-Pair or 6-Pair (Non-Armored)
	Black	0.41 (10)	5-Pair or 6-Pair (Armored)
8000737 4.5" (114) harness (floating hook terminal)	Silver	0.30 (8)	2-Pair or 3-Pair (Armored and Non-Armored)
8000738 4.5" (114) harness (floating hook terminal)	Yellow	0.36 (9)	5-Pair or 6-Pair (Non-Armored)
	Black	0.41 (10)	5-Pair or 6-Pair (Armored)
800011296 4.5" (114) harness (floating hook terminal w/ 1/4" stud hole)	Yellow	0.36 (9)	5-Pair or 6-Pair (Non-Armored)
	Black	0.41 (10)	5-Pair or 6-Pair (Armored)
8000739 7" (177) harness (floating hook terminal)	Silver	0.30 (8)	2-Pair or 3-Pair (Armored and Non-Armored)
8000740 (long neck)	Silver	0.30 (9)	2-Pair or 3-Pair (Armored and Non-Armored)
	Black	0.41 (10)	5-Pair or 6-Pair (Armored and Non-Armored)
8000744* 7" (177) harness (floating hook terminal)	Yellow	0.36 (9)	5-Pair or 6-Pair (Armored and Non-Armored)
	Black	0.41 (10)	5-Pair or 6-Pair (Armored and Non-Armored)
8000746 14" (365) harness (floating hook terminal)	Silver	0.30 (8)	2-Pair or 3-Pair (Armored and Non-Armored)
8000747 14" (365) harness (floating hook terminal)	Yellow	0.36 (9)	5-Pair or 6-Pair (Armored and Non-Armored)
	Black	0.41 (10)	5-Pair or 6-Pair Double Sheath Armored and Non-Armored)
8000748 2.75" (69) harness (floating special)	Black	0.41 (10)	5-Pair or 6-Pair (Armored and Non-Armored)
8000749 4.5" (114) harness (floating ring terminal)	Silver	0.30 (8)	2-Pair or 3-Pair
8000750 4.5" (114) harness (floating ring terminal)	Yellow	0.36 (9)	5-Pair or 6-Pair
	Black	0.41 (10)	5-Pair or 6-Pair (Armored and Non-Armored)
8000752 4.5" (114) harness (floating hook terminal)	Aluminum	0.56 (14)	12-Pair (Armored and Non-Armored)
8000753 7" (178) (floating ring terminal)	Black	0.43 (11)	Fiber Optic Drop Cables

