

TAP™ Protector Rod



Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

TAP™ Protector Rods are intended to protect the conductor from potential damage due to bolted or compression type hot line clamp and stirrup installation. These rods provide reinforcement to the conductor, designed to reduce the possibility of conductor damage due to bending stress, clamping stress, or abrasion.

Features

- Reduces clamping stress on the conductor
- Manufactured from strong, fatigue resistant aluminum alloy
- RUS-approved product for standard construction methods
- Easily installed by hand or hot sticks
- Limited conductor preparation required for installation

Documentation

Application Procedures

[SP-2685 \(TAP™ Protector Rod\)](#)

Catalog Pages

[TAP™ Protector Rod - Catalog](#)

Sales Materials

[TAP™ Protector Rod - Sell Sheet](#)

Part Tables

TAP Protector Rods						
PLP Catalog Number	RUS Approved Conductors	TAP Rod Conductor Ranges	Total Diameter Tap Rod & Conductor	Applied Length	Color	Qty. per Carton
TAP-0175	#4 ACSR, AAC, AAAC	.244" - .259"	.486" - .501"	10"	Orange	25
TAP-0179	#2 ACSR, AAC, AAAC	.309" - .326"	.551" - .568"	10"	Red	25
TAP-0183	1/0 ACSR, AAC, AAAC	.390" - .413"	.632" - .655"	12"	Yellow	25
TAP-0185	2/0 ACSR, AAC, AAAC	.437" - .463"	.679" - .705"	13"	Blue	25
TAP-0187	3/0 ACSR, AAC, AAAC	.491" - .521"	.733" - .763"	14"	Orange	25
TAP-0189	4/0 ACSR, AAC, AAAC	.552" - .585"	.764" - .827"	15"	Red	25
TAP-0191	266.8 ACSR, AAC, AAAC	.607" - .630"	.849" - .872"	16"	White	25
TAP-0192	266.8 ACSR, AAC, AAAC	.632" - .655"	.874" - .897"	16"	Yellow	25
TAP-0194	336.4 ACSR, AAC, AAAC	.680" - .703"	.922" - .945"	17"	Blue	25
TAP-0195	336.4 ACSR, AAC, AAAC	.704" - .740"	.946" - .982"	18"	Green	25
TAP-0197	477 ACSR, AAC, AAAC	.793" - .840"	1.035" - 1.082"	20"	Purple	25
TAP-0198	477 ACSR, AAC, AAAC	.841" - .898"	1.083" - 1.140"	21"	Blue	25