

FIBERLIGN® Dielectric Dead - End Short Span Series

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Documentation

See Pages 3-3 [Communication Catalogue](#)

Part Tables

Part Number	ADSS Diameter Range (mm)
ADSSTS-075-S	7.5 - 8.3
ADSSTS-084-S	8.4 - 9.2
ADSSTS-093-S	9.3 - 10.1
ADSSTS-102-S	10.2 - 10.8
ADSSTS-109-S	10.9 - 11.5
ADSSTS-116-S	11.6 - 12.3
ADSSTS-124-SG	12.4 - 12.9
ADSSTS-130-SG	13.0 - 13.7
ADSSTS-138-SG	13.8 - 14.6
ADSSTS-147-SG	14.7 - 15.3
ADSSTS-154-SG	15.4 - 16.0
ADSSTS-161-SG	16.1 - 16.9
ADSSTS-170-SG	17.0 - 17.9
ADSSTS-180-SG	18.0 - 18.9
ADSSTS-210-SG	21.0 - 21.9
ADSSTS-220-SG	22.0 - 22.9

Note: Recommended for ADSS spans up to 200m. Subject to ADSS cable design and operating conditions. May be used for "Medium Span" applications, contact PLP for recommendations.