



GLAS-GRIP® DEAD-END AND GLAS-SPLICE

The **GLAS-GRIP Dead-End** and **GLAS-SPLICE** are designed specifically for fiberglass rod. They are intended to be used on transmission, antenna, communications, and other types of guyed structures that require the use of insulated down guys.

FEATURES AND BENEFITS

- Glas-Grip Dead-Ends are designed to develop the published rated strength of the fiberglass rod that it is applied to
- Use Glas-Grip Dead-Ends and Glas-Splices to make custom-length insulated guy wires
- Glas-Grips are not interchangeable with dead-ends that are designed for fiberglass strand or metal guy strand



ORDERING INFORMATION

GLAS-GRIP Dead-End

Catalog Number	Fiberglass Rod		Per Carton		Length	Color Code
	Size Solid	Mean Diameter				
	in	in	Units	Wt/lb	in	
DER-2168	5/16"	.337"	50	64	34	Orange
DER-2169	3/8"	.400"	25	51	40	Yellow
DER-2171	1/2"	.525"	10	44	53	Green
DER-2173	5/8"	.670"	5	40	68	Black

NOTES:

1. Recommended for use with Fiberglass Rod having the diameter as shown in the chart above.
2. Refer to the Application Procedure, picture no. 1 for recommended protection of the Fiberglass Rod when using a come-along.
3. GLAS-GRIP Dead-End is not interchangeable with Dead-Ends that are designed for Fiberglass Strand or metal guy strand.

GLAS-SPLICE

Catalog Number	Fiberglass Rod		Per Carton		Length	Color Code
	Size Solid	Mean Diameter				
	in	in	Units	Wt/lb	in	
GSR-2130	1/4"	.290"	50	53	37	Red
GSR-2131	5/16"	.337"	50	54	50	Orange
GSR-2132	3/8"	.400"	25	68	60	Yellow
GSR-2134	1/2"	.525"	10	73	79	Green
GSR-2136	5/8"	.670"	5	66	101	Black