




PREFORMED LINE PRODUCTS
The connection you can count on.

SWAN-FLIGHT™ DIVERTER



-  COMMUNICATIONS
-  ENERGY
-  SPECIAL INDUSTRIES
-  SOLAR





PLP® Distribution Products SWAN-FLIGHT™ DIVERTER

Description

The Preformed Line Products SWAN-FLIGHT Diverter is designed for use on overhead conductors to create greater visibility for avian flight paths on overhead lines and tower down guys. Offering little wind resistance, it reduces hazards to both lines and birds. For low and medium voltage construction, apply the SWAN-FLIGHT Diverter to phase conductors (bare or jacketed). For high voltages, it is typically used on shield wire.

The SWAN-FLIGHT Diverter is lightweight, offers little wind resistance and is easily and quickly applied by hand or hot stick. The positive grip on the conductor is designed to ensure that the SWAN-FLIGHT Diverter remains in the applied location and does not move along the span under Aeolian vibration or other conditions.

Materials

Manufactured from rigid high impact polyvinyl chloride (PVC), the SWAN-FLIGHT Diverter possesses excellent chemical resistance, strength properties and will retain good physical characteristics within a range of extreme temperatures. Industrial fumes and salt water cannot seriously degrade the properties of rigid PVC.

Spacing

For optimal results, spacing distances are generally recommended at 15' intervals,

depending upon local conditions. Since wind resistance is very limited, sufficient SWAN-FLIGHT Diverters can be used to ensure adequate visibility without creating stresses on the line. When marking adjacent spans, overall visibility is improved by staggering the placement between the spans.

Features

SWAN-FLIGHT Diverters are designed to offer the following advantages:


- Increased conductor profile to provide increased visibility where large, slow moving bird flight paths are present
- Economical and easily applied
- Lightweight
- Long service life without deterioration of material properties
- Minimal wind resistance
- Manufactured from gray or yellow high impact PVC with UV protection

Visibility

The diverter section increases the visible profile of the cable or conductor to ensure safety, but avoids an undesirable bulky outline.

Application

Ensure the correct size SWAN-FLIGHT Diverter is used. For detailed installation description, refer to the application procedure. Hot stick application is fast and simple with standard equipment.



SWAN-FLIGHT Diverter - Product Data							
PLP Catalog Number	Conductor Range (Inches)		Overall Length (Inches)	Diameter of Diverter Coil (Inches)	Diameter of PVC Rod (Inches)	Approx. Weight (lbs)	Color Code
	Min	Max					
SFD-0445	0.175	0.249	20	7.0	0.375	0.40	Black
SFD-0635	0.250	0.349	23	7.0	0.375	0.46	Blue
SFD-0890	0.350	0.449	25	7.5	0.375	0.50	Brown
SFD-1140	0.450	0.599	35	8.0	0.375	0.70	Green
SFD-1520	0.600	0.770	38	8.0	0.500	1.40	Purple
SFD-1960	0.771	0.858	38	8.0	0.500	1.40	Red
SFD-2220	0.859	0.942	40	8.0	0.500	1.50	Orange
SFD-2460	0.943	1.121	40	8.0	0.500	1.50	Pink
SFD-2700	1.122	1.306	40	8.0	0.500	2.00	Gray*
SFD-3035	1.307	1.530	46	8.0	0.500	2.00	Black

*Gray is the standard color. For yellow add "-Y" after the catalog number.
For voltage over 230kv, add "-B" for black semi-conductive material.



**PREFORMED
LINE PRODUCTS**

World Headquarters
660 Beta Drive
Cleveland, Ohio 44143

Mailing Address:
P.O. Box 91129
Cleveland, Ohio 44101

Telephone: 440.461.5200
Fax: 440.442.8816
Web Site: www.preformed.com
E-mail: inquiries@preformed.com

© 2011 Preformed Line Products
Printed in U.S.A.
EN-SS-1076-1
09.11.00