

**MATERIAL SAFETY
DATA SHEET
UI-9909**

**PREFORMED LINE PRODUCTS
URETHANE DIVISION
1700 Woodhurst Lane
Albemarle, North Carolina 28001
704-983-6161**

Emergency Phone Number: Chemtrec 800-424-9300 (within the USA), 202-483-7616 (outside of the USA.) Call only in the event of a chemical emergency involving spill, leak, fire exposure, or accident involving chemicals.

SECTION 1 - CHEMICAL PRODUCT

PRODUCT NAME: UI-9909
PRODUCT USE/CLASS: Primer
REVISED: 12/27/04

SECTION 2 - Composition / Information on Ingredients

<u>Chemical Name</u>	<u>CAS No.</u>	<u>Weight % Less than</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH TLV-STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL- CEILING</u>	<u>Units</u>	<u>Skin</u>
Toluene	108-88-3	75%	50	N.E	200	300	ppm	S
N-Butanol	71-36-3	5.0%	N.E.	C 50	100	N.E.	ppm	S
2-Butoxyethanol	111-76-2	4.0%	25	N.E.	50	N.E.	ppm	S
Ethyl Alcohol	64-17-5	4.0%	1000	N.E.	1000	N.E.	ppm	

N.E. – Not Established, S – Skin Designation, C – Ceiling

SECTION 3 - HAZARDS IDENTIFICATION

****Emergency Overview**:** Clear liquid, with Solvent odor. Flammable liquid and vapor. Harmful if absorbed through skin. May cause skin and eye irritation. May cause respiratory tract irritation. Vapor harmful; may affect the brain or nervous system causing dizziness, headache or nausea.

Effects of overexposure – Eye Contact : May cause eye irritation.

Effects of overexposure – Skin Contact: May be absorbed through the skin in harmful amounts. May cause skin irritation. May cause dermatitis.

Effects of Overexposure – Inhalation: Possible irritation of the respiratory system can occur causing a variety of symptoms such as dryness of the throat, tightness of the chest, and shortness of breath. May cause central nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma. May cause headache & nausea.

Effects of Overexposure – Ingestion: Harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

Effects of Overexposure – Chronic Hazards: May cause liver or kidney damage. Repeated or prolonged solvent overexposure may result in permanent central nervous system damage. May affect the blood and blood-forming organs. Chronic skin contact may cause dermatitis.

Primary Route(s) of Entry: Skin Contact, Skin absorption, Inhalation, Ingestion, Eye Contact

4 First-aid measures

First Aid – Eye contact: Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

First Aid – Skin Contact: Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

First Aid – Inhalation: Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

First Aid – Ingestion: If swallowed, do not induce vomiting. Give victim one or two glasses of water or milk. Call a physician or poison control center immediately for further instructions. Never give anything by mouth to an unconscious person.

**MATERIAL SAFETY
DATA SHEET
UI-9909**

**PREFORMED LINE PRODUCTS
URETHANE DIVISION
1700 Woodhurst Lane
Albemarle, North Carolina 28001
704-983-6161**

5 Fire-fighting measures

Flash Point: 35F, 2C
(Setaflash Closed Cup)

Lower explosive limit (%): 1.10
Upper explosive limit (%): 19.00

Autoignition Temperature: N.D.

OSHA Flammability Classification: Flammable Liquid – Class IB

Extinguishing Media: Carbon Dioxide, Dry Chemical, Foam, Water Fog

Unusual Fire and Explosion Hazards: Flammable liquid and vapor. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, open flame, and other sources of ignition. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool.

Special Firefighting Procedures: Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water spray may be ineffective. If water is used, fog nozzles are preferable. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

6 Accidental release measures

Steps to be taken in case material is released or spilled: Keep non-essential personnel a safe distance away from the spill area. Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid breathing vapors. Use self-contained breathing equipment. Notify appropriate authorities if necessary. Contain and remove with inert absorbent material and non-sparking tools. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the MSDS form.

7 Handling and storage

Handling: Keep closure tight and container upright to prevent leakage. Ground and bond containers when transferring material. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation. Because empty containers may retain product residue and flammable vapors, keep away from heat, sparks and flame; do not cut, puncture or weld on or near the empty container. Do not smoke where this product is used or stored.

Storage: Do not store or use near heat, sparks, or open flame. Refer to OSHA 29CFR Part 1910.106 "Flammable and Combustible Liquids" for specific storage requirements. Store only in well-ventilated areas. Do not puncture, drag or slide container. Keep container closed when not in use.

8 Exposure controls and personal protection

Engineering Controls: Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits. Caution: Solvent vapors are heavier than air and collect in lower levels of the work area. Sufficient ventilation (using explosion-proof equipment) should be provide to prevent flammable vapor/air mixtures from accumulating.

Respiratory Protection: Use a NIOSH/OSHA approved chemical/mechanical filter respirator designed to remove a combination of particulates and organic vapor if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. Observe OSHA regulation (29CFR 1910.134) for respirator use.

Skin Protection: Use neoprene, nitrile, or rubber gloves to prevent skin contact.

Eye Protection: Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

Other protective Equipment: Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

**MATERIAL SAFETY
DATA SHEET
UI-9909**

**PREFORMED LINE PRODUCTS
URETHANE DIVISION
1700 Woodhurst Lane
Albemarle, North Carolina 28001
704-983-6161**

Hygienic Practices: Wash hands before eating, smoking, or using toilet facility. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

9 Physical and Chemical Properties

Boiling Range:	172-340 F	Vapor Density:	Heavier than air
Appearance:	Clear	Evaporation Rate:	Slower than Ether
Physical State:	Liquid	Density, LB/GL:	7.46
Odor:	Solvent	Specific Gravity:	0.90
Solubility in H2O:	Insoluble	pH:	N.A.
Freeze Point:	N.D.	Odor Threshold:	N.D.
Volatile by weight:	87.1%	Volatile by Volume:	90.4%
Vapor Pressure:	N.D.		
Coefficient of water/oil			
Distribution:	N.D.		

(See section 16 for abbreviation legend)

10 Stability and reactivity

Conditions to avoid: High temperatures. Sources of ignition.

Incompatibility: Strong acids, bases, and strong oxidizers.

Hazardous decomposition products: Carbon monoxide, carbon dioxide.

Hazardous Polymerization: Hazardous polymerization will not occur under normal conditions.

Stability: Product is stable under normal storage conditions.

11 Toxicological information

Product LD50 (Oral) : No Data
(Dermal) : No Data
Product LC50 : No Data

12 Ecological information

Ecological Information: No information

13 Disposal considerations

Disposal Method: Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

14 Transportation information

DOT Proper Shipping Name: Adhesive
DOT Hazard Class: 3
DOT UN/NA Number: UN 1133
Packing Group: II
Emergency Response Guide Number: 127

**MATERIAL SAFETY
DATA SHEET
UI-9909**

**PREFORMED LINE PRODUCTS
URETHANE DIVISION
1700 Woodhurst Lane
Albemarle, North Carolina 28001
704-983-6161**

15 Regulatory information

U.S. Federal Regulations: As Follows-

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

SARA Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS Number	WT% is less than
Toluene	108-88-3	75%
N-Butanol	71-36-3	5.0%
2-Butoxyethanol	111-76-2	4.0%

Toxic Substances Control Act:

Inventory Status:

The chemical substances in this product are on the TSCA Section 8 Inventory.

Export Notification:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States.

Chemical Name	CAS Number
Acetone	67-64-1

16 Other information

HMIS Ratings – Health: 2* Flammability: 3 Reactivity: 0
*indicates a chronic hazard; see section 3

Reason for revision: Revised Section 9 and 16

Volatile Organic Compounds (Calculated): 6.49 lbs/gal, 778 grams/ltr

Legend: N.A.- Not applicable, N.E. – Not Established, N.D. – Not Determined

990191340R

Disclaimer

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.