

Prevent outages and protect wildlife  
with PREFORMED™ Wildlife Protectors.



## Wildlife Protectors are made from a durable plastisol material that stands up to UV rays, lasts longer, and protects better.

### Various configurations

Several different Wildlife Protectors are available to meet specific configuration needs. Whether you have a single bushing transformer or a CSP transformer, Preformed Line Products has a Wildlife Protector that suits your application.

### Strong materials

Our Wildlife Protectors are made from a light grey, high voltage, plastisol compound that is a minimum of 125 mils thick. This material contains ultraviolet stabilizers and fungicides and has a dielectric strength of 240 v/mil. This allows for durable operation and prevents wildlife-induced outages.

### Simple installation

Wildlife Protectors are available for either new construction or retrofit applications. Wildlife Protectors are applied by hand



without any special tools. If needed, Wildlife Protectors can be easily trimmed in the field. Certain Wildlife Protectors are designed with locking tabs to easily and securely attach them to bushings.

### You can depend on PLP®

We have been committed to being a dependable supplier since 1947. All PREFORMED™ products are backed by

extensive laboratory and field test data. Our sales and engineering staff are dedicated to on-going research and development to bring the most reliable products to the field. If you have special design requirements, or would like additional information regarding Wildlife Protectors, please contact PLP today.

Wildlife Protectors		
Catalog Number	Carton Quantity	Description
WP-18T	50	Used for single bushing transformers and for capacitors. Locking tabs hold protector on first skirt of insulator.
WP-17T	50	Used for single bushing transformers and for capacitors. Locking tabs hold protector on first skirt of insulator.
WP-11S	50	Used for covering existing line or as retrofit application. There is no need to disconnect primary lead to install the protector. Slit down the side. Fasteners enable it to be held in place.
WP-CSP	25	Used on CSP transformers. Specially designed to protect both primary bushing and lightning arrester. Also for retrofit application. No need to disconnect primary lead to install protector.
WP-12 x 12	25	Fits under bottom skirt of insulator on single bushing and CSP transformers. High density black PVC- 12" x 12" x 1/8". Covers top of transformer.
WP-GRE	8	Used for dead-front capability for UG sectionalizers and switches. Also for single bushing transformers and capacitors. Locking tabs hold Wildlife Protector on first skirt of insulator. Tube opening is 1-1/2" for maximum cable size.
WP-2.25F	25	Used for single bushing transformers. Covers 2-1/4" O.D. current limiting fuse bolted to bushing. The ring indicates point to cut off excess material slipped over the fuse.

**PREFORMED**  
LINE PRODUCTS



P.O. Box 91129  
Cleveland, Ohio 44101

440.461.5200

Fax: 440.442.8816

www.preformed.com

inquiries@preformed.com