



PREFORMED LINE PRODUCTS
The connection you can count on.

COYOTE[®] DTC8 (Drop Termination Closure) 8 Grommet Design



COMMUNICATIONS




ENERGY



SPECIAL INDUSTRIES



SOLAR



PLP® Fiber Optic Products

COYOTE® DTC8 (Drop Termination Closure)

Description

Fiber network design strategy is critical to the long term success of the service provider. The ideal FTTH network configuration calculates all factors of current and future growth and no assumptions are required. In reality, network design is full of complex decisions, requiring assumptions, balanced between quality, reliability, deployment efficiency and cost. Selecting the right fiber optic closure for network deployment is also a balance of these factors but one critical factor cannot be dismissed - application flexibility.

Welcome the COYOTE DTC8, the new largest member of the DTC (Drop Termination Closure) family. The COYOTE DTC8 provides the ultimate level of application flexibility for fiber drop distribution applications. The closure can be configured with a range of fiber organizer systems to support splice, distributed splitter and drop applications using traditional cable, blown fiber cable, pushable drop cable technology or microtube cable. Organizers to support pre-connectorized drop applications as an alternative to more costly proprietary hardened drop cable systems are also available.

Key Features:

- **Size:** 12" x 8.8" x 3.5"
(305 x 225 x 90 mm)
- **Max Splice Capacity:** 48
- **Max Adapter Capacity:** See table for adapter options
- **Grommet Quantity:** 8 – See table for grommet options
- Flexible grommet sealing system supports a wide range of flat or round cable profiles
- Factory installed sealing materials
- Reenterable and reusable
- Designed to GR-771 Generic Requirements for Fiber Splice Closures
- Constructed with flame retardant UV stabilized material
- Hinged collar system provides quick access. No special tools required.
- IP-68 Rated



Grommet View



No Organizer



Splice Organizer



Splice Organizer




Splice + Adapters



Splice + Adapters





Splice + Adapters




Adapter Organizer

PLP® Fiber Optic Products
COYOTE® DTC8 (Drop Termination Closure)
 Installation Environments




**SPLICE ORGANIZER
 PROTECTED STORAGE**



SPLICE + ADAPTERS

COYOTE® DTC8 Ordering Instructions

Catalog Number Example: DTC8-BBDD-CCCC-2-2-1-2-Y

DTC8		XXXX		XXXX		X		X		X		X		X		
Grommet Selection Select 4	Cable Diameter Range	Grommet Selection Select 4	Cable Diameter Range	Organizer Options Select 1	Splice Tray Selection Selection/ Quantity	Adapter Type Select 1	Adapter Quantity	Pigtails Required Select 1 (Matches adapter type and quantity)								
A	SOLID / PLUG	A	SOLID / PLUG	NONE	N	NONE	N	NONE								
B	.170" - .220" (4.3 - 5.6 mm) ROUND CABLES	B	.170" - .200" (4.3 - 5.1 mm) ROUND CABLES	1 Splice Only - Protected Storage	1 to 4 	Dual SCAPC	0 to 4	Y								
C	.220" - .270" (5.6 - 6.9 mm) ROUND CABLES	C	.250" - .350" (6.4 - 8.9 mm) ROUND CABLES													
D	.270" - .320" (6.9 - 8.1 mm) ROUND CABLES	D	.156" - .170" (4.0 mm - 4.3 mm) ROUND CABLES	2 Splice + Adapters	1 to 4	Dual SCUJPC	2	Y								
E	.320" - .370" (8.1 - 9.4 mm) ROUND CABLES	E	.093" - .125" (2.4 - 3.2 mm) ROUND CABLES													
F	.370" - .420" (9.4 - 10.7 mm) ROUND CABLES	F	FLAT DROP CABLE	3 Splice Only - Open Storage	1 to 4	Quad LCAPC	3	Y								
G	.420" - .470" (10.7 - 11.9 mm) ROUND CABLES	G	.350" - .400" (8.9 - 10.2 mm) ROUND CABLES													
H	.470" - .550" (11.9 - 14.0 mm) ROUND CABLES			4 Adapters Only			4	Y								
J	.156" - .170" (4.0 mm - 4.3 mm) ROUND DROP CABLES															
K	.093" - .125" (2.4 - 3.2 mm) ROUND DROP CABLES															
L	2 FLAT DROP CABLES															

Accessories

Catalog No.	Description
8004104	DTC8 Pole/Wall Mount Bracket
8004105	DTC8 Cable Storage Bracket Kit
8004111	DTC4/6/8 Aerial Strand Bracket
8004112	DTC4/6/8 ADSS Bracket
8004108	DTC8 Pedestal Bracket Kit - For use with Channell Commercial Corp. 10" x 22" Round Pedestal



World Headquarters 660 Beta Drive Cleveland, Ohio 44143 Mailing Address: P.O. Box 91129 Cleveland, Ohio 44101
 Telephone: 440.461.5200 Fax: 440.442.8816 www.preformed.com E-mail: inquiries@preformed.com
 © 2017 Preformed Line Products Printed in U.S.A. CO-SS-1147-3 08-17-H

