





PLP® Distribution Products

TAP™ PROTECTOR RODS

Description

TAP™ Protector Rods are applied on the conductor where bolted hot line tap clamps are to be installed. TAP Protector Rods provide reinforcement to the conductor, designed to reduce the possibility of conductor damage due to bending stress, clamping stress, or abrasion.

TAP™ Protector Rods are for aluminum based conductors.

- Manufactured from strong, fatigue resistant aluminum alloy
- RUS-approved product for standard construction methods

Application


- Easily installed by hand or hot sticks
- Limited conductor preparation required

Features

- Better current transfer capabilities
- Reduces clamping stress on the conductor
- Lightweight
- Minimum rod lengths



TAP Protector Rods						
PLP Catalog Number	RUS Approved Conductors	TAP Rod Conductor Ranges	Total Diameter Tap Rod & Conductor	Applied Length	Color	Qty. per Carton
TAP-0175	#4 ACSR, AAC, AAAC	.244"259"	.486"501"	10"	Orange	25
TAP-0179	#2 ACSR, AAC, AAAC	.309"326"	.551"568"	10"	Red	25
TAP-0183	1/0 ACSR, AAC, AAAC	.390"413"	.632"655"	12"	Yellow	25
TAP-0185	2/0 ACSR, AAC, AAAC	.437"463"	.679"705"	13"	Blue	25
TAP-0187	3/0 ACSR, AAC, AAAC	.491"521"	.733"763"	14"	Orange	25
TAP-0189	4/0 ACSR, AAC, AAAC	.552"585"	.764"827"	15"	Red	25
TAP-0191	266.8 ACSR, AAC, AAAC	.607"630"	.849"872"	16"	White	25
TAP-0192	266.8 ACSR, AAC, AAAC	.632"655"	.874"897"	16"	Yellow	25
TAP-0194	336.4 ACSR, AAC, AAAC	.680"703"	.922"945"	17"	Blue	25
TAP-0195	336.4 ACSR, AAC, AAAC	.704"740"	.946"982"	18"	Green	25
TAP-0197	477 ACSR, AAC, AAAC	.793"840"	1.035" - 1.082"	20"	Purple	25
TAP-0198	477 ACSR, AAC, AAAC	.841"898"	1.083" -1.140"	21"	Blue	25





World Headquarters 660 Beta Drive Cleveland, Ohio 44143

Mailing Address: P.O. Box 91129 Cleveland, Ohio 44101

Telephone: 440.461.5200 Fax: 440.442.8816 Web Site: www.preformed.com E-mail: inquiries@preformed.com

© 2015 Preformed Line Products Printed in U.S.A. EN-ML-1040 11.15.2.5C