





ENERGY





SPECIAL INDUSTRIES



읝 SOLAR









18" - 20" Cable Loop



Uni-Group Cable Guide



Abrasion Protectors



World Headquarters 660 Beta Drive Cleveland, Ohio 44143

Mailing Address: P.O. Box 91129 Cleveland, Ohio 44101

Telephone: 440.461.5200 Fax: 440.442.8816 Web Site: www.preformed.com E-mail: inquiries@preformed.com

© 2011 Preformed Line Products Printed in U.S.A. CO-SS-1037-2 08.11.5C

## PLP Fiber Optic Products

## FIBERLIGN® CLAS Storage - PATENTED

# Center-Lock Aerial Slack Storage System for All-Dielectric Self Supporting (ADSS) Cables

The FIBERLIGN Center-Lock Aerial Slack (CLAS) Storage System provides In-Span storage for ADSS cables up to 1" (25mm) in diameter. It is designed to maximize ease of installation, accept a wide range of cable sizes, and allow for cable only or butt splice applications.

#### **Features**


- Centerlock hinge design
- Heavy duty UV resistant strap fasteners no metal fasteners
- Dual purpose apertures
- Expansion tabs
- Abrasion protector or Uni-Group Cable Guide (UCG)

#### **Benefits**

- Swing open at center lock-hinge and rest on top of main cable for convenient positioning and simple attachment.
- Long hinge design distributes load along cable interface
- Folds and separates at the hinge for efficient storage
- Minimized labor and installation time straps cinch quickly and secure to the main cable eliminating the need for tools and metal fasteners
- Safe with all dielectric materials with superior system life
- Straps secure cable and lock cable storage bracket through common aperture
- Expansion tabs allow 20" (508 mm) maximum loop diameter storage
- Abrasion protectors economical protection for cable passing the pole
- UCG guides cable past the pole through Low Profile applications between communication and utility zones
- UCG Designed for banded (metal pole) or lagged (wood pole) applications - no extra brackets required

### **Installation Options**

- For Stainless Steel strapping, elastomer tubing can be ordered to build surface contact when securing the CLAS Bracket. See Filler Tube.
- 18" (457mm) cable loop diameters are stored against the cable channel.
- For butt splice applications, the expansion tabs provide support for an outer cable loop wrap, or for large cables, and over and under cable loop configuration.



Aerial Closure Bracket Kits	Option
No Brackets	Blank
Classic COYOTE PUP, 6"x22", and 8.5"x22"	С
Classic COYOTE RUNT	R
COYOTE In-Line RUNT Closure	R1
Stainless Steel Splice Case	S
6.5" COYOTE Dome Option	D1

Pole Pass Type	Option
Abrasion Protectors	Α
Uni-Group Cable Guide	U
Extra Cable Ties	Option
No Extra Ties (10 included in kit)	Blank
25 Extra Heavy Duty Cable Ties	T1
Filler Tube <.5" - 20" long, 20 pack	Catalog No. 699912980



COYOTE Dome Bracket Kit